


Radha Wall Light Fitting

INSTRUCTION MANUAL

Safety Warnings

- This product is only suitable for connection to a 240V~50Hz supply in accordance with current IEE wiring regulations, and should be installed in accordance with local building regulations. It is for domestic ceiling use only, and is not suitable for a bathroom location.
- Before installing your light fitting always switch off the mains supply and remove the appropriate fuse or switch off the appropriate circuit breaker before commencing installation.
- This fitting is a Class II, Double Insulated product  and does not require an Earth. Live or Neutral must not be connected to Earth.
- Never fit bulbs of a higher wattage than those specified on the label (as these may cause overheating and damage the fitting).
- If the mains cable becomes damaged it must only be replaced by a technically competent, qualified person.
- Allow 10 minutes to cool before replacing, adjusting or cleaning. Clean with a dry cloth only. Do not use liquid or abrasive cleaners on this product.
- If you are in any doubt about your competence please consult a qualified electrician.
- If any modification is made it will invalidate the warranty and may render the product unsafe.

Care Information

Allow 10 minutes to cool before replacing, adjusting or cleaning.
Clean with a dry cloth only. Do not use liquid or abrasive cleaners on this product.

Assembly / User Instructions

Before you start

Please read these instructions carefully before fitting and retain for reference. Check the packaging and make sure that you have all the required parts. Follow each assembly step in order to prevent incorrect assembly.

The Light pack contains:

Light fitting
Fixing pack

The following tools may be required:

Selection of cross and flat head screwdrivers.
Electric drill and assorted drill bits.
Wire strippers.
Electrical insulation tape

These assembly diagrams are intended as a guide – if in doubt consult a qualified electrician.

1. Decide on the position of the light fitting or remove existing light fitting. Note the position of the electrical connections, and ensure there is a solid mounting surface, Preferably a wooden joist or joist bridge, to support the weight of the light fitting.
2. Measure the distance between the fixing holes on the product to determine the correct location for the fixings. Ensure there is a joist at the point of fixing to support the weight of the product. Take care to avoid damaging any concealed wiring and pipes.
3. Insert the fixing pack (A) to the holes drilled in point 2.
4. Support your fitting and connect the house wiring to the terminal block – see expanded wiring details in installation drawing. **NOTE: This is a Class II fitting and must NOT be earthed. Ensure no loose strands are left out of the connection block.**
5. Secure the wall plate (C) to the wall by using the supplied screws (B). Once product is fixed in position, hand tighten the screw caps onto the screws.

Assembly / User Instructions Continued

6. Fit the bulbs. **NOTE: Never fit bulbs of a higher wattage than those specified on the label (as these may cause over heating and damage the fitting).**
7. The lampshade part can be adjusted by (D) to an appropriate angle as needed.
8. Turn on the power and test.

